

Disk	OS 10-12		OS 10-18				OS 20-28				OS 30-36			
Width (m)	10	12	10	12	15	16	18	20	21	24	24	27	28	30
Blade position	$\frac{78/95}{3,4}$	$\frac{78/95}{1,3,4}$	$\frac{78/95}{1,3}$	$\frac{78/95}{1,3}$	$\frac{78/95}{1,2,3}$	$\frac{78/95}{1,2,3}$	$\frac{75/95}{3}$	$\frac{75/95}{3}$	$\frac{75/95}{3}$	$\frac{78/95}{1,3}$	$\frac{70/94}{3}$	$\frac{72/95}{3}$	$\frac{72/95}{3}$	$\frac{73/95}{1,2,3}$

- 1 - Disk speed 870 rev/min
- 2 - Coupling height: a= 100 cm, b=100cm
- 3 - Lift the spoilers on all blades
- 4 - Coupling height: a=90cm, b=96cm

		Position of applicator hatches											
		kg/ha											
Width		3	4	5	6	7	8	9	10	11	12		
10	8 km/h		4				5		6		7		
	10 km/h	4			5		6		7				
	12 km/h	4		5		6		7					
12	8 km/h		4			5		6		7			
	10 km/h	4		5		6		7					
	12 km/h	4,5	5		6	7							
15	8 km/h	4		5		6		7					
	10 km/h	4,5	5		6	7							
	12 km/h		5	6	7								
16	8 km/h	4	4,5	5	6	6,5	7	7,5	8	8,5	9		
	10 km/h	4,5	5	6	6,5	7	8	8,5	9				
	12 km/h	5	4	7	7,5	8	9						
18	8 km/h	4,5	5	5,5	6	7	7,5	8	8,5	9			
	10 km/h		5	6	7	8	8,5	9					
	12 km/h	5	6	7	8	9							
20	8 km/h	4,5	5	6	6,5	7	8	8,5	9				
	10 km/h	5	6	7	7,5	8	9						
	12 km/h	6	7	8	8,5	9							
21	8 km/h	4,5	5	6	7	7,5	8	8,5	9				
	10 km/h	5	6	7	8	9							
	12 km/h	6	7	8	9								
24	8 km/h	5	6	7	7,5	8	9						
	10 km/h	6	7	8	8,5	9							
	12 km/h	6	7	8	9								
27	8 km/h	5	6	7		7,5	8						
	10 km/h	6	7	7,5	8								
	12 km/h	6	7	8									
28	8 km/h	5	6	7	7,5	8							
	10 km/h	6	7	7,5	8								
	12 km/h	6	7	8									
30	8 km/h	5	6	7	7,5	8							
	10 km/h	6,5	7	7,5	8								
	12 km/h	7	7,5	8									

General Terms & Conditions
 Values for settings given for spreaders and micro-pellet dispensers are provided as an indication only. Slug pellets may respond differently according to weather conditions (moisture levels in particular). Experience shows that spreaders available on the market can also vary considerably in their functioning – even if the same settings are used. In order to avoid quantities applied differing from those required and to ensure that application is consistent, DE SANGOSSE recommends that each user check the settings against output.

IRONMAX^{PRO}, AMM No. 2160226 - Composition: Ferric Phosphate IP^{MAX} 3%. Registered brands, authorization to place on market and manufacture: DE SANGOSSE. Please read all labels carefully before use and strictly observe all best practices, quantities, conditions for use and safety precautions. Authorized usage, instructions and quantities: please refer to the manual and label and/or www.desangosse.fr and/or www.phytodata.com. DE SANGOSSE SAS with a capital of EUR 9 828 225 - 300163 896 RCS Agen – Intra-Community VAT No. FR 57 300163 896 DE SANGOSSE - Bonnel - 47480 PONT DU CASSE Authorization No. AQ01561 for the distribution of plant production products for professional use. July 2016 – Cancels and replaces any previous version. Current updated version of product factsheets available from www.ciblage-anti-limaces.fr

PRODUCTS FOR PROFESSIONALS: USE PLANT PROTECTION PRODUCTS WITH CARE. BEFORE USE, PLEASE READ LABELS AND PRODUCT INFORMATION.