



| DSX / DSX-W / DSX-W GEOs | pread | 12M | | | |
|--------------------------|----------------|----------------|--|--|--|
| | | | | | |
| PTO speed | 410 | | | | |
| Disc speed | 540 | | | | |
| Spreader angle | Horizontal | N / X | | | |
| Booms | 285 /285 / 285 | | | | |
| Low-volume kit | Yes | 0 0 7 | | | |
| GEOpoint | 6.5 m | | | | |
| FIELD-EDGE SPREADING | Eco settings | Yield settings | | | |
| PTO speed | | | | | |
| Disc speed | | | | | |
| TrimFlow position | | | | | |

| 9.5 AN | | | $\overline{\mathbf{x}}$ | Application rate (kg/hectare) | | | | | | |
|--------|--------|-----|-------------------------|-------------------------------|--------|--------|---------|---------|---------|---------|
| - | kg/min | VI. | kg/min | 6 km/h | 8 km/h | 9 km/h | 10 km/h | 11 km/h | 12 km/h | 14 km/h |
| 6+3 | 0,31 | F | 1,00 | 8,3 | 6,3 | 5,6 | 5,0 | 4,5 | 4,2 | 3,6 |
| 6+4 | 0,39 | G | 1,30 | 10,8 | 8,1 | 7,2 | 6,5 | 5,9 | 5,4 | 4,6 |
| 6+5 | 0,52 | G | 1,70 | 14,2 | 10,6 | 9,4 | 8,5 | 7,7 | 7,1 | 6,1 |
| 12+0 | 0,62 | G | 2,00 | 16,7 | 12,5 | 11,1 | 10,0 | 9,1 | 8,3 | 7,1 |
| 12+1 | 0,89 | G | 2,50 | 20,8 | 15,6 | 13,9 | 12,5 | 11,4 | 10,4 | 8,9 |
| 12+2 | 1,15 | Н | 3,00 | 25,0 | 18,8 | 16,7 | 15,0 | 13,6 | 12,5 | 10,7 |
| 12+3 | 1,29 | Н | 3,20 | 26,7 | 20,0 | 17,8 | 16,0 | 14,5 | 13,3 | 11,4 |
| 12+4 | 1,47 | Н | 3,50 | 29,2 | 21,9 | 19,4 | 17,5 | 15,9 | 14,6 | 12,5 |

General Terms & Conditions

Slug pellets may respond differently according to weather conditions (moisture levels in particlalar). Experience shows that spreaders available on the market can also vary considerably in their functioning — even if the same settings are used. In order to avoid quantities applied differing from those required and to ensure that application is consistent, DE SANGOSSE recommends that each user check the settings against output. Values for settings given for spreaders and micro-pellet dispensers are provided as an indication only.

IRONMAX® PRO, AMM No. 2160226 - Composition: Ferric Phosphate IP^{MAX} 3 %. Registered brands, authorization to place on market and manufacture: DE SANGOSSE. Please read all labels carefully before use and strictly observe all best practices, quantities, conditions for use and safety precautions. Authorized usage, instructions and quantities: please refer to the manual and label and/or www.desangosse.fr and/or www. phytodata.com. DE SANGOSSE SAS with a capital of EUR 9 828 225 - 300163 896 RCS Agen — Intra-Community VAT No. FR 57 300163 896 DE SANGOSSE - Bonnel - 47480 PONT DU CASSE Authorization No. AQ01561 for the distribution of plant production products for professional use. July 2016 — Cancels and replaces any previous version. Current updated version of product factsheets available from www.ciblage-anti-limaces.fr